



**MATERIAL SAFETY DATA SHEET
(MECHSTER™ 9000TA)
PRE-ACCELERATED THIXOTROPIC ORTHOPHTHALATE
POLYESTER RESIN**

PAGE 1 OF 4

SECTION – 1: PRODUCT IDENTIFICATION

- 1.1 CHEMICAL NAME/SYNONYM : UNSATURATED POLYESTER RESIN SOLUTION IN STYRENE
- 1.2 BRAND / TRADE NAME : PRE-ACCELERATED THIXOTROPIC ORTHOPHTHALATE POLYESTER RESIN MECHSTER 9000TA
- 1.3 CHEMICAL COMPOSITION : Orthophthalic acid based polyester resin solution in Styrene.
- 1.4 MANUFACTURER'S NAME AND ADDRESS : MECHEMCO INDUSTRIES
Unit No. 27, Kewal Industrial Estate
Senapati Bapat Marg, Lower Parel
Mumbai 400 013. INDIA
- 1.5 EMERGENCY TELEPHONE NOS. : +91-22-24966373/24966374/24951799
FAX NO. : +91-22-24945907
E-MAIL ADDRESS : mechemco@vsnl.com

SECTION – 2: HAZARDOUS INGREDIENTS

INGREDIENT	WT%	CAS No.	EEC No.	TLV
Styrene	40-50%	100-42.5	601-026-00-0	100 ppm (8 hr reference period)

SECTION – 3: PHYSICAL DATA

- 3.1 STATE : Viscous Liquid
- 3.2 COLOUR : Hazy Rose colour
- 3.3 ODOUR : Styrene Odour
- 3.4 FLASH POINT : 34°C (Styrene)
- 3.5 SPECIFIC GRAVITY : 1.11
- 3.6 VISCOSITY at 30 °C : 400-600 cP, Thixotropic
- 3.7 WATER SOLUBILITY : Insoluble in Water

SECTION – 4: STORAGE AND HANDLING INFORMATION

- 4.1 STORAGE : Keep tightly closed in a dry, cool and well ventilated place. Protect against heat
- 4.2 HANDLING : Protection against fire and explosion. Keep away from sources of ignition.
"NO SMOKING"



**MATERIAL SAFETY DATA SHEET
(MECHSTER™ 9000TA)
PRE-ACCELERATED THIXOTROPIC ORTHOPHTHALATE
POLYESTER RESIN**

PAGE 2 OF 4

SECTION – 5: HAZARDS IDENTIFICATION AND DATA

- 5.1 MOST IMPORTANT HAZARDS : Flammable
5.2 FIRE & EXPLOSION HAZARD : Dangerous fire hazard & moderate explosion hazard when vapour is exposed to flame
5.3 HAZARD DATA : Harmful by inhalation, irritation to eyes & skin
a. Threshold Limit Value : 100 ppm (8 hours reference period)
b. Effects of Over Exposure : May cause skin and eye irritation
-

SECTION – 6: FIRE FIGHTING MEASURES

- 6.1 Extinguishing Media : Standard procedures for Chemical fire, use dry powder, sand, foam. Cool the containers / tanks with water spray
6.2 Special Notes : May form toxic materials, viz., Carbon Dioxide, Carbon Monoxide and various hydrocarbons while burning. Recommended to Wear self contained breathing apparatus while fighting fire
-

SECTION – 7: STABILITY AND REACTIVITY DATA

- 7.1 STABILITY : Store below 30 °C in closed original Containers. Store in dark, away from Oxidising Materials
7.2 CONDITIONS TO AVOID : Excess heating or cooling over long time, exposure to sunlight, mixing with strong oxides
7.3 HAZARDOUS DECOMPOSITION PRODUCTS : None under normal use. Thermal decomposition can lead to release of irritating gases and vapours
7.4 HAZARDOUS POLYMERIZATION : May occur
-

SECTION – 8: TOXICOLOGICAL INFORMATION

No information available



**MATERIAL SAFETY DATA SHEET
(MECHSTER™ 9000TA)
PRE-ACCELERATED THIXOTROPIC ORTHOPHTHALATE
POLYESTER RESIN**

PAGE 3 OF 4

SECTION – 9: EMERGENCY FIRST AID PROCEDURES

- 9.1 EYE CONTACT : Flush eyes with copious amount of water for at least 15 minutes. Seek medical attention if irritation persists
- 9.2 SKIN CONTACT : Wash skin with water and soap. Seek medical attention if irritation persists
- 9.3 INHALATION : Move to fresh air. Restore or support breathing as required. Keep the person warm and at rest. Seek medical attention as soon as possible
- 9.4 INGESTION : If conscious, give large quantities of water and contact physician

SECTION – 10: EMPLOYEE PROTECTION / SPECIAL PROTECTION

- 10.1 RESPIRATORY PROTECTION : In case of insufficient ventilation wear suitable respiratory equipment
- 10.2 VENTILATION : Mechanical ventilation and local exhaust
- 10.3 OTHER PROTECTIVE EQUIPMENT
- a) Hands Protection : PVC or other plastic material gloves
 - b) Eye Protection : Splash Proof Goggles / Face Shield
 - c) Skin / Body Protection : Chemical Resistant Apron, Protective Suit, Safety Shoes / Boots

SECTION – 11: DISPOSAL INFORMATION / ENVIRONMENT PROTECTION

- 11.1 SPILL AND LEAK PROCEDURES : Soak up with inert adsorbent material. Shovel in to suitable container for disposal. After cleaning, flush away traces with water.
- 11.2 WASTE DISPOSAL METHOD : Incinerate or land-fill in accordance with local pollution regulation and ordinance.
- 11.3 ENVIRONMENTAL HAZARDS : Non specified

SECTION – 12: ECOLOGICAL INFORMATION

- 12.1 GENERAL INFORMATION : Marine Pollutant
- 12.2 DISPOSAL METHODS : Refer to SECTION 11 for safe disposal



**MATERIAL SAFETY DATA SHEET
(MECHSTER™ 9000TA)
PRE-ACCELERATED THIXOTROPIC ORTHOPHTHALATE
POLYESTER RESIN**

PAGE 4 OF 4

SECTION – 13: REGULATORY INFORMATION

13.1	OSHA REGULATION	100 ppm for Styrene (As per Section 2)
13.2	ACGIH	50 ppm for short term exposure limit for Styrene
13.4	SAFETY PRECAUTIONS	Refer to Section 4 and Section 8

SECTION – 14: SPECIAL PRECAUTIONS

14.1	PRECAUTION ON HANDLING AND STORING	: Flammable. Keep away from heat, sparks and open flame
------	---------------------------------------	--

SECTION – 15: TRANSPORT INFORMATION

15.1	MARINE POLLUTANT	: Yes
15.2	CLASS	: 3
15.3	UN NO.	: 1866
15.4	PROPER SHIPPING NAME	: Resin Solution