
SECTION – 1: PRODUCT & COMPANY IDENTIFICATION

1.1	CHEMICAL NAME/SYNONYM	: UNSATURATED POLYESTER RESIN SOLUTION IN STYRENE
1.2	BRAND / TRADE NAME	: ORTHOPHTHALATE RESIN MECHSTER 9000W-V1
1.3	CHEMICAL COMPOSITION	: Orthophthalic acid based polyester resin solution in Styrene.
1.4	MANUFACTURER'S NAME AND ADDRESS	: MECHEMCO RESINS PVT. LTD. D-36/3, T.T.C INDUSTRIAL AREA, MIDC, TURBHE, NAVI MUMBAI – 400 613. INDIA.
1.5	EMERGENCY TELEPHONE NOS. FAX NO. E-MAIL ADDRESS	: +91-22-27682720 / 27632153 / 27632154 : +91-22-27682721 : mechemcoresins@vsnl.net / mrpl@mtnl.net.in

SECTION – 2: INFORMATION ON HAZARDOUS INGREDIENTS

INGREDIENT	WT%	CAS No.	EEC No.	TLV
Styrene	30-45%	100-42.5	601-026-00-0	100 ppm (8 hr reference period)

SECTION – 3: EMERGENCY FIRST AID PROCEDURES

3.1	EYE CONTACT	Flush eyes with copious amount of water for at least 15 minutes. Seek medical attention if irritation persists
3.2	SKIN CONTACT	Wash skin with water and soap. Seek medical attention if irritation persists
3.3	INHALATION	Move to fresh air. Restore or support breathing as required. Keep the person warm and at rest. Seek medical attention as soon as possible
3.4	INGESTION	If conscious, give large quantities of water and contact physician.

SECTION – 4: FIRE AND EXPLOSION DATA

4.1	THE PRODUCT IS	Flammable liquid, Class IC.
4.2	AUTO IGNITION TEMPERATURE	490°C Styrene
4.3	FLASH POINT	34°C Styrene
4.4	FLAMMABLE LIMITS	LOWER: 0.9% UPPER: 6.8% (Styrene)

- | | | |
|-----|--------------------------------------|--|
| 4.5 | PRODUCTS OF COMBUSTION | May produce carbon monoxide, carbon dioxide, and irritating or toxic vapors, gases or particulate. |
| 4.6 | FIRE HAZARD | Flammable in the presence of open flames, sparks, or heat. |
| 4.7 | EXPLOSION HAZARD | Can react with oxidizing materials. Explosive in the form of vapor when exposed to heat or flame. Material may polymerize when container is exposed to heat (fire) and polymerization will increase pressure in a closed container which may cause the container to rupture violently. |
| 4.8 | FIRE FIGHTING MEDIA AND INSTRUCTIONS | SMALL FIRE: Use carbon dioxide, foam, dry chemical or water fog to extinguish.
LARGE FIRE: Evacuate surrounding areas. Use carbon dioxide, foam, dry chemical or water fog to extinguish. Wear self-contained breathing apparatus (SCBA) and full fire fighting protective clothing. Cool containing vessels with water spray in order to prevent pressure build-up, auto ignition or explosion. Prevent run off to sewers or other water ways. |

SECTION – 5: ACCIDENTAL RELEASE MEASURES

- | | | |
|-----|-------------|---|
| 5.1 | SMALL SPILL | Absorb with an inert material and place in an appropriate waste disposal container. |
| 5.2 | LARGE SPILL | Stop leak if without risk. Eliminate all ignition sources. Contain with an inert material, recover as much as possible and place the remainder in an appropriate waste disposal container. Warn unauthorized personnel to move away. Prevent entry into sewers or confined areas. |

SECTION – 6: STORAGE AND HANDLING INFORMATION

- | | | |
|-----|----------|---|
| 6.1 | STORAGE | Keep tightly closed in a dry, cool and well ventilated place. Protect against heat |
| 6.2 | HANDLING | Protection against fire and explosion. Keep away from sources of ignition. "NO SMOKING" |

SECTION – 7: EMPLOYEE PROTECTION / SPECIAL PROTECTION

- | | | |
|-----|----------------------------|---|
| 7.1 | RESPIRATORY PROTECTION | : In case of insufficient ventilation wear suitable respiratory equipment |
| 7.2 | VENTILATION | : Mechanical ventilation and local exhaust |
| 7.3 | OTHER PROTECTIVE EQUIPMENT | |
| | a) Hands Protection | : PVC or other plastic material gloves |
| | b) Eye Protection | : Splash Proof Goggles / Face Shield |
| | c) Skin / Body Protection | : Chemical Resistant Apron, Protective Suit, Safety Shoes / Boots |

SECTION – 8: PHYSICAL AND CHEMICAL PROPERTIES

8.1	PHYSICAL STATE	Viscous Liquid
8.2	COLOUR	Clear Colorless to Pale Yellow
8.3	MOLECULAR WEIGHT (d/mol)	1000 to 15000
8.4	MELTING POINT	Not available
8.5	VAPOR PRESSURE	4.5 mm Hg @ 20°C (Styrene)
8.6	ODOUR	Styrene Odor (Aromatic)
8.7	EVAPORATION RATE	Not available
8.8	WATER SOLUBILITY	Insoluble in Water
8.9	pH (1% soln / water)	Not applicable
8.10	BOILING POINT	145°C (Styrene)
8.11	SPECIFIC GRAVITY	1.10 – 1.14
8.12	VAPOR DENSITY	3.59 (Styrene)
8.13	WATER/OIL dist. coeff.	Not available
8.14	DISPERSION PROPERTIES	Not dispersed in water.

SECTION – 9: STABILITY AND REACTIVITY DATA

9.1	STABILITY	This product is normally stable, but can become unstable at elevated temperatures.
9.2	INSTABILITY TEMPERATURE	77°C
9.3	CONDITIONS OF HEAT	Heat-up
9.4	INCOMPATIBILITY WITH VARIOUS SUBSTANCES	Polymerizes in the presence of organic peroxides, oxidizing materials, or heat.
9.5	CORROSIVITY	No specific information is available in our database regarding the corrosivity of this product in presence of various materials.



SECTION – 10: TOXICOLOGICAL INFORMATION

10.1	ROUTES OF ENTRY	Inhalation, Ingestion, Skin Contact, Eye contact.
10.2	TOXICITY TO ANIMALS	1) Styrene Lung effects have been observed in mouse studies following repeated exposures.

SECTION – 11: ECOLOGICAL INFORMATION

ECOTOXICITY	Toxic to aquatic organisms. Should not be released to sewage system or other bodies of water at concentrations above limits established in regulations or permits.
-------------	--

SECTION – 12: TRANSPORT INFORMATION

12.1	DOT – SHIPPING DESCRIPTION	UN1866; RESIN SOLUTION; 3; III	 
12.2	TDG - SHIPPING DESCRIPTION	UN1866; RESIN SOLUTION; 3; III	
12.3	IATA/IMDG – SHIPPING DESCRIPTION	IATA: UN1866; RESIN SOLUTION; 3; III; Pkg. Inst.: Passenger – 309; CARGO – 310. IMDG: UN1866; RESIN SOLUTION; 3; III; FLASH POINT: 31°C; EMS No.: F-E, S-E	

SECTION – 13: REGULATORY INFORMATION

OTHER REGULATIONS	This section does not reference all applicable regulatory compliance lists. OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200) SARA 302 component(s): None. SARA 313 component(s): Styrene (100ppm), Cobalt Compounds.
-------------------	--



SECTION – 14: SPECIAL PRECAUTIONS

14.1	PRECAUTION ON HANDLING AND STORING	Flammable. Keep away from heat, sparks and open flame
------	------------------------------------	---

SECTION – 15: DISPOSAL INFORMATION

15.1	SPILL AND LEAK PROCEDURES	Soak up with inert adsorbent material. Shovel in to suitable container for disposal. After cleaning, flush away traces with water.
15.2	WASTE DISPOSAL METHOD	Incinerate or land-fill in accordance with local pollution regulation and ordinance.

SECTION – 16: OTHER INFORMATION

NFPA (USA)	HMIS (USA)	Protective Clothing								
<p data-bbox="414 485 456 510">Fire</p>  <p data-bbox="277 611 342 636">Health</p> <p data-bbox="529 611 630 636">Reactivity</p> <p data-bbox="358 709 505 735">Specific hazard</p>	<table border="1"><tbody><tr><td data-bbox="711 537 1079 583">Health hazards</td><td data-bbox="998 537 1079 583">2</td></tr><tr><td data-bbox="711 583 1079 630">Fire hazard</td><td data-bbox="998 583 1079 630">3</td></tr><tr><td data-bbox="711 630 1079 676">Reactivity</td><td data-bbox="998 630 1079 676">1</td></tr><tr><td data-bbox="711 676 1079 722">Personal protection</td><td data-bbox="998 676 1079 722">X</td></tr></tbody></table>	Health hazards	2	Fire hazard	3	Reactivity	1	Personal protection	X	<p data-bbox="1182 443 1442 468">Protective Clothing</p> 
Health hazards	2									
Fire hazard	3									
Reactivity	1									
Personal protection	X									