



**MATERIAL SAFETY DATA SHEET  
(MECHSTER 9000G)  
ORTHOPHTHALATE POLYESTER GELCOAT RESIN**

PAGE 1 OF 4

**SECTION – 1: PRODUCT IDENTIFICATION**

1.1	CHEMICAL NAME/SYNONYM	: UNSATURATED POLYESTER RESIN SOLUTION IN STYRENE
1.2	BRAND / TRADE NAME	: ORTHOPHTHALATE POLYESTER GELCOAT RESIN MECHSTER 9000G
1.3	CHEMICAL COMPOSITION	: Orthophthalate Polyester resin solution in Styrene.
1.4	MANUFACTURER'S NAME AND ADDRESS	: MECHEMCO INDUSTRIES Unit No. 27, Kewal Industrial Estate Senapati Bapat Marg, Lower Parel Mumbai 400 013. INDIA
1.5	EMERGENCY TELEPHONE NOS. FAX NO. E-MAIL ADDRESS	: +91-22-24966373/24966374/24951799 : +91-22-24945907 : mechemco@vsnl.com

**SECTION – 2: HAZARDOUS INGREDIENTS**

INGREDIENT	WT%	CAS No.	EEC No.	TLV
Styrene	30-40	100-42.5	601-026-00-0	100 ppm (8 hr reference period)

**SECTION – 3: PHYSICAL DATA**

3.1	STATE	: Highly Viscous Liquid
3.2	COLOUR	: Opaque
3.3	ODOUR	: Styrene Odour
3.4	FLASH POINT	: 34°C (Styrene)
3.5	SPECIFIC GRAVITY	: 1.12
3.6	VISCOSITY at 30 °C	: 1800-2400 cp
3.7	WATER SOLUBILITY	: Insoluble in Water

**SECTION – 4: STORAGE AND HANDLING INFORMATION**

4.1	STORAGE	: Keep tightly closed in a dry, cool and well ventilated place. Protect against heat
4.2	HANDLING	: Protection against fire and explosion. Keep away from sources of ignition. "NO SMOKING"



**MATERIAL SAFETY DATA SHEET  
(MECHSTER 9000G)  
ORTHOPHTHALATE POLYESTER GELCOAT RESIN**

PAGE 2 OF 4

---

**SECTION – 5: HAZARDS IDENTIFICATION AND DATA**

- |     |                             |   |
|-----|-----------------------------|---|
| 5.1 | MOST IMPORTANT HAZARDS      | : Flammable   |
| 5.2 | FIRE & EXPLOSION HAZARD     | : Dangerous fire hazard & moderate explosion hazard when vapour is exposed to flame |
| 5.3 | HAZARD DATA                 | : Harmful by inhalation, irritation to eyes & skin                                  |
|     | a. Threshold Limit Value    | : 100 ppm (8 hours reference period)  |
|     | b. Effects of Over Exposure | : May cause skin and eye irritation   |

---

**SECTION – 6: FIRE FIGHTING MEASURES**

- |     |                     |  |
|-----|---------------------|--|
| 6.1 | Extinguishing Media | : Standard procedures for Chemical fire, use dry powder, sand, foam. Cool the containers / tanks with water spray  |
| 6.2 | Special Notes       | : May form toxic materials, viz., Carbon Dioxide, Carbon Monoxide and various hydrocarbons while burning. Recommended to Wear self contained breathing apparatus while fighting fire |

---

**SECTION – 7: STABILITY AND REACTIVITY DATA**

- |     |                                  |  |
|-----|----------------------------------|--|
| 7.1 | STABILITY                        | : Store below 30 °C in closed original Containers. Store in dark, away from Oxidising Materials    |
| 7.2 | CONDITIONS TO AVOID              | : Excess heating or cooling over long time, exposure to sunlight, mixing with strong oxides        |
| 7.3 | HAZARDOUS DECOMPOSITION PRODUCTS | : None under normal use. Thermal decomposition can lead to release of irritating gases and vapours |
| 7.4 | HAZARDOUS POLYMERIZATION         | : May occur  |

---

**SECTION – 8: TOXICOLOGICAL INFORMATION**

No information available



**MATERIAL SAFETY DATA SHEET  
(MECHSTER 9000G)  
ORTHOPHTHALATE POLYESTER GELCOAT RESIN**

PAGE 3 OF 4

---

**SECTION – 9: EMERGENCY FIRST AID PROCEDURES**

- 9.1 EYE CONTACT : Flush eyes with copious amount of water for at least 15 minutes. Seek medical attention if irritation persists
- 9.2 SKIN CONTACT : Wash skin with water and soap. Seek medical attention if irritation persists
- 9.3 INHALATION : Move to fresh air. Restore or support breathing as required. Keep the person warm and at rest. Seek medical attention as soon as possible
- 9.4 INGESTION : If conscious, give large quantities of water and contact physician

---

**SECTION – 10: EMPLOYEE PROTECTION / SPECIAL PROTECTION**

- 10.1 RESPIRATORY PROTECTION : In case of insufficient ventilation wear suitable respiratory equipment
- 10.2 VENTILATION : Mechanical ventilation and local exhaust
- 10.3 OTHER PROTECTIVE EQUIPMENT
- a) Hands Protection : PVC or other plastic material gloves
  - b) Eye Protection : Splash Proof Goggles / Face Shield
  - c) Skin / Body Protection : Chemical Resistant Apron, Protective Suit, Safety Shoes / Boots

---

**SECTION – 11: DISPOSAL INFORMATION / ENVIRONMENT PROTECTION**

- 11.1 SPILL AND LEAK PROCEDURES : Soak up with inert adsorbent material. Shovel in to suitable container for disposal. After cleaning, flush away traces with water.
- 11.2 WASTE DISPOSAL METHOD : Incinerate or land-fill in accordance with local pollution regulation and ordinance.
- 11.3 ENVIRONMENTAL HAZARDS : Non specified

---

**SECTION – 12: ECOLOGICAL INFORMATION**

- 12.1 GENERAL INFORMATION : Marine Pollutant
- 12.2 DISPOSAL METHODS : Refer to SECTION 11 for safe disposal



**MATERIAL SAFETY DATA SHEET  
(MECHSTER 9000G)  
ORTHOPHTHALATE POLYESTER GELCOAT RESIN**

PAGE 4 OF 4

---

**SECTION – 13: REGULATORY INFORMATION**

---

13.1	OSHA REGULATION	100 ppm for Styrene (As per Section 2)
13.2	ACGIH	50 ppm for short term exposure limit for Styrene
13.4	SAFETY PRECAUTIONS	Refer to Section 4 and Section 8

---

**SECTION – 14: SPECIAL PRECAUTIONS**

---

14.1	PRECAUTION ON HANDLING AND STORING	: Flammable. Keep away from heat, sparks and open flame
------	---------------------------------------	--

---

**SECTION – 15: TRANSPORT INFORMATION**

---

15.1	MARINE POLLUTANT	: Yes
15.2	CLASS	: 3
15.3	UN NO.	: 1866
15.4	PROPER SHIPPING NAME	: Resin Solution

---